



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 11.02.2011

Revision 10.02.2011 (GB) Version 6.0

Bio-Fluid-Spray (GB)

1. Identification of the substance/mixture and of the company/undertaking

Product identifier

Name of product

Bio-Fluid-Spray (GB)
Code-Nr. 116000

Manufacturer/distributor

WEICON GmbH & Co. KG
Königsberger Straße 255, DE-48157 Münster
Postbox 84 60, DE-48045 Münster
Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322-244
E-Mail : info@weicon.de
Internet : www.weicon.de

Advice

Abteilung Angebote, Verkauf, Export
Phone ++49(0)251 / 9322 - 0

Emergency advice

Giftnotruf Bonn: Bei Vergiftungen (in case of poisoning)
Phone ++49(0)228-19 240

Recommended intended purpose(s)

Technical Aerosols

2. Hazards identification

Classification according to 67/548/EEC or 1999/45/EC

F+; R12

R-phrases

12 Extremely flammable.

Labelling according to 67/548/EEC or 1999/45/EC

Remarks for labelling

The product is classified and labelled in accordance with EC directives/German regulations on dangerous substances.

F+ Extremely flammable

R-phrases

12 Extremely flammable.

S-phrases

51 Use only in well-ventilated areas.

9 Keep container in a well-ventilated place.

Special rules for supplemental label elements for certain mixtures

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Without sufficient ventilation the formation of explosive vapour/air mixtures cannot be excluded. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

Information pertaining to special dangers for human and environment

In extensive use, formation of flammable / explosive vapour-air mixture is possible.



3. Composition/information on ingredients

Description

Medical white oil, containing additives, in aerosol can. Propellant: propane / butane

Hazardous ingredients

| CAS No | EC No | Name | [% weight] | Classification according to 67/548/EEC |
|------------|-------|------------------------|------------|----------------------------------------|
| 61641-74-5 | | propane/butane-mixture | 40-45 | F+, R12 |

4. First aid measures

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Ensure of fresh air.

In case of skin contact

In case of contact with skin wash off with warm water.

In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

In case of ingestion

If swallowed or in case of vomiting, danger of infiltration into the lungs (danger of aspiration).

Refer to medical treatment.

Physician's information / possible symptoms

The following symptoms may occur:

Delirious state

Anaesthetic state

Headache

Confusion

Dizziness

5. Firefighting measures

Suitable extinguishing media

Foam

Dry powder

Carbon dioxide

Extinguishing media which must not be used for safety reasons

water

Special hazards arising from the substance or mixture

Danger of bursting

Fire gas of organic material has to be classed invariably as respiratory poison.

Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply.

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Additional information

Cool endangered containers with water spray jet.



6. Accidental release measures

Personal precautions

Ensure adequate ventilation.
Keep away sources of ignition.

Environmental precautions

Do not discharge into the drains or bodies of water..

Methods for cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

Additional Information

Sort out leaky cans and dispose according to regulations.

7. Handling and storage

Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Advice on protection against fire and explosion

Do not spray on a naked flame or any incandescent material.
Pressurized container.
Do not pierce or burn even after use.
The product is combustible.
Vapours can form an explosive mixture with air.
Avoid effect of heat.

Requirements for storage rooms and vessels

Keep in closed original container.
Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

Further information on storage conditions

Protect from direct solar radiation.
Keep container in a well-ventilated place
Storage temperature may not exceed 50°C (=122°F).
Keep in a cool place.

8. Exposure controls/personal protection

Ingredients with occupational exposure limits to be monitored

| CAS No | Name | Code | [mg/m ³] | [ppm] | Remark |
|----------|--------|------------|----------------------|-------|-----------|
| 106-97-8 | Butane | 8 hours | 1450 | 600 | EH40/2005 |
| | | Short-term | 1810 | 750 | |

Respiratory protection

If ventilation insufficient, wear respiratory protection.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]:: Nitrile rubber; 0,4mm; 480min;60min.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Eye protection

safety goggles

Skin protection

protective clothing

**Bio-Fluid-Spray (GB)****General protective measures**

Do not inhale gases/vapours/aerosols.

Hygiene measures

At work do not eat, drink, smoke or take drugs.

9. Physical and chemical properties**Form**
aerosol**Colour**
colourless, clear**Odour**
solvent-like**Important health, safety and environmental information**

| | Value | Temperature | at | Method | Remark |
|----------------------------|----------------|-------------|----|--------|-------------------|
| Flash point | not applicable | | | | |
| Vapour pressure | 3,5 bar | 20 °C | | | Doseninnendruck |
| Solubility in water | | | | | partially soluble |

Explosive properties

The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .

10. Stability and reactivity**Conditions to avoid**

Keep away from heat.

Formation of explosive gas/air mixtures.

Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Thermal decomposition

Remark No decomposition if used as directed.

11. Toxicological information**Acute toxicity/Irritability/Sensitization**

| | Value/Validation | Species | Method | Remark |
|---------------------------|------------------|---------|--------|--------|
| Irritability skin | non-irritant | | | |
| Irritability eye | non-irritant | | | |
| Skin sensitization | non-sensitizing | | | |

Experiences made from practice

Inhalation causes narcotic effect/intoxication.



12. Ecological information

General regulation

Do not allow uncontrolled leakage of product into the environment.
Product is not allowed to be discharged into aquatic environment.

13. Disposal considerations

Waste code No.

15 01 10*

Name of waste

packaging containing residues of or contaminated by dangerous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 91/689/EEC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Totally emptied packaging may be treated as household waste.

General information

For proper waste disposal a complete emptying of the tin is necessary.

14. Transport information

Land and inland navigation transport ADR/RID

UN 1950 AEROSOLS, 2.1, (D), Classification code: 5F
transport in "limited quantities" according to 3.4 ADR LQ2 is possible

Marine transport IMDG

UN 1950 AEROSOLS, 2.1

Air transport ICAO/IATA-DGR

UN 1950 Aerosols, flammable, 2.1

Transport/further information

24h EMERGENCY CONTACT (TRANSPORT) +49(0)178 433 7434 (Consultank Lutz Harder GmbH)

15. Regulatory information

VOC standard

VOC value

305,4 g/L

16. Other information

Recommendend uses and restrictions

National and local regulations concerning chemicals shall be observed.

Further information

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Wording of the R/H-phrases specified in chapter 3 (not the classification of the mixture!)

R 12 Extremely flammable.