



1. Identification of the substance/mixture and of the company/undertaking

Product identifier

Name of product Easy-Mix N 50 Resin (GB)
Code-Nr. 106511

Manufacturer/distributor

WEICON GmbH & Co. KG
Königsberger Straße 255, DE-48157 Münster
Postbox 84 60, DE-48045 Münster
Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322-244
E-Mail : info@weicon.de
Internet : www.weicon.de

Advice

Abteilung Angebote, Verkauf, Export
Phone ++49(0)251 / 9322 - 0

Emergency advice

Giftnotruf Bonn: Bei Vergiftungen (in case of poisoning)
Phone ++49(0)228-19 240

Recommended intended purpose(s)

2-Component Epoxy Resin - Resin Component

2. Hazards identification

Classification according to 67/548/EEC or 1999/45/EC

Xi; R36/38

R43

N; R51/53

R-phrases

36/38

Irritating to eyes and skin.

43

May cause sensitisation by skin contact.

51/53

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Labelling according to 67/548/EEC or 1999/45/EC

Remarks for labelling

The product is classified and labelled in accordance with EC directives/German regulations on dangerous substances.

Xi Irritant

N Dangerous for the environment

R-phrases

36/38

Irritating to eyes and skin.

43

May cause sensitisation by skin contact.

51/53

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S-phrases

2

Keep out of the reach of children.

24

Avoid contact with skin.

26

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

37/39

Wear suitable gloves and eye/face protection.

46

If swallowed, seek medical advice immediately and show this container or label.

51

Use only in well-ventilated areas.



Hazardous ingredients for labeling

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)

Special rules for supplemental label elements for certain mixtures

Contains epoxy constituents. See information supplied by the manufacturer.

3. Composition/information on ingredients

Description

Resin for a two-component epoxy adhesive

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to 67/548/EEC
25068-38-6	500-033-5	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	50 - 100	Xi R36/38; R43; N R51-53

4. First aid measures

General information

Remove contaminated soaked clothing immediately and dispose it safely.

In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with soap and water.

In case of eye contact

May cause superficial burns.

In case of contact with eyes rinse thoroughly with water.

Seek medical advice immediately.

In case of ingestion

Do not induce vomiting.

Call for a doctor immediately.

If swallowed by mistake drink plenty of water and seek medical treatment.

Treatment (Advice to doctor)

In the event of pulmonary irritation treat initially with dexamethasone metered-dose aerosol.

5. Firefighting measures

Suitable extinguishing media

Foam

Dry fire-extinguishing substance

Carbon dioxide

Water spray jet

water mist

Extinguishing media which must not be used for safety reasons

Full water jet

Special hazards arising from the substance or mixture

Fire gas of organic material has to be classed invariably as respiratory poison.

Carbon monoxide (CO)

Carbon dioxide (CO2)

Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply.



Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

6. Accidental release measures

Personal precautions

Use personal protective clothing.

Environmental precautions

Do not discharge into the drains/surface waters/groundwater.
Do not discharge into the subsoil/soil.

Methods for cleaning up

Send in suitable containers for recovery or disposal.
Take up with absorbent material.

7. Handling and storage

Advice on safe handling

Avoid formation of aerosols.
Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.
Open and handle container with care!

Advice on protection against fire and explosion

Pay attention to general rules of internal fire prevention.

Requirements for storage rooms and vessels

Keep in closed original container.

Advice on storage compatibility

Do not store together with animal feedstuffs.
Do not store together with food.

Further information on storage conditions

Store container at cool and aired place.

8. Exposure controls/personal protection

Respiratory protection

Breathing apparatus in the event of aerosol or mist formation.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: natural rubber, 0,6mm; 480min; 60min;

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Eye protection

tightly fitting goggles

Skin protection

protective clothing

General protective measures

Avoid contact with eyes and skin
Do not inhale gases/vapours/aerosols.

Hygiene measures

At work do not eat, drink and smoke.
Wash hands before breaks and after work.



13. Disposal considerations

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Uncontaminated packaging may be treated as household waste.

14. Transport information

Land and inland navigation transport ADR/RID

UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (BISPHENOL A EPOXY HARZ), 9, III, (E),
Classification code: M7

Marine transport IMDG

UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (BISPHENOL A EPOXY RESIN), 9, III, Marine Pollutant

Air transport ICAO/IATA-DGR

UN 3077 Environmentally hazardous substance, solid, n.o.s. (BISPHENOL A EPOXY RESIN), 9, III

Transport/further information

24h EMERGENCY CONTACT (TRANSPORT) +49(0)178 433 7434 (Consultank Lutz Harder GmbH)

15. Regulatory information

16. Other information

Recommend uses and restrictions

National and local regulations concerning chemicals shall be observed.

Further information

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Wording of the R/H-phrases specified in chapter 3 (not the classification of the mixture!)

R 36/38 Irritating to eyes and skin.

R 43 May cause sensitisation by skin contact.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.