



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 11.02.2011

Revision 10.02.2011 (GB) Version 6.0

Freeze-Spray (GB)

1. Identification of the substance/mixture and of the company/undertaking

Product identifier

Name of product Freeze-Spray (GB)
Code-Nr. 116100

Manufacturer/distributor

WEICON GmbH & Co. KG
Königsberger Straße 255, DE-48157 Münster
Postbox 84 60, DE-48045 Münster
Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322-244
E-Mail : info@weicon.de
Internet : www.weicon.de

Advice

Abteilung Angebote, Verkauf, Export
Phone ++49(0)251 / 9322 - 0

Emergency advice

Giftnotruf Bonn: Bei Vergiftungen (in case of poisoning)
Phone ++49(0)228-19 240

Recommended intended purpose(s)

Technical Aerosols

2. Hazards identification

Classification according to 67/548/EEC or 1999/45/EC

F+; R12

R-phrases

12 Extremely flammable.

Labelling according to 67/548/EEC or 1999/45/EC

Remarks for labelling

The product is classified and labelled in accordance with EC directives/German regulations on dangerous substances.

F+ Extremely flammable

R-phrases

12 Extremely flammable.

S-phrases

23 Do not breathe spray.
51 Use only in well-ventilated areas.
9 Keep container in a well-ventilated place.

Special rules for supplemental label elements for certain mixtures

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Without sufficient ventilation the formation of explosive vapour/air mixtures cannot be excluded. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

Information pertaining to special dangers for human and environment

In extensive use, formation of flammable / explosive vapour-air mixture is possible.



3. Composition/information on ingredients

Description

Preparation based on propellant mixture.

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to 67/548/EEC
61641-74-5		propane/butane-mixture	90-100	F+, R12

4. First aid measures

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.
Ensure of fresh air.

In case of skin contact

In case of contact with skin wash off with water.

In case of eye contact

In case of contact with eyes rinse thoroughly with water.

In case of ingestion

Do not induce vomiting.
Medical treatment.

Physician's information / possible symptoms

The following symptoms may occur:
Anaesthetic state
Headache

Treatment (Advice to doctor)

Treat symptoms.
If necessary, give oxygen.

5. Firefighting measures

Suitable extinguishing media

Foam
Dry powder
Carbon dioxide

Extinguishing media which must not be used for safety reasons

water

Special hazards arising from the substance or mixture

Fire gas of organic material has to be classed invariably as respiratory poison.

Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply.
Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Additional information

Cool endangered containers with water spray jet.



6. Accidental release measures

Personal precautions

Ensure adequate ventilation.
Use personal protective clothing.
Keep away sources of ignition.

Methods for cleaning up

Allow to vaporise.

7. Handling and storage

Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking
Do not spray on a naked flame or any incandescent material.
Do not pierce or burn even after use.
The product is combustible.
Vapours can form an explosive mixture with air.
Formation of explosive gas mixtures in air.

Requirements for storage rooms and vessels

Keep in closed original container.
Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

Further information on storage conditions

Protect from heat and direct solar radiation.
Keep container in a well-ventilated place
Storage temperature may not exceed 50°C (=122°F).
Store container at cool and aired place.
Keep in a cool place.

8. Exposure controls/personal protection

Ingredients with occupational exposure limits to be monitored

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
106-97-8	Butane	8 hours	1450	600	EH40/2005
		Short-term	1810	750	

Respiratory protection

In case of insufficient ventilation or long-term effect use breathing apparatus.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: Nitrile rubber; 0,4mm; 480min;60min.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Eye protection

safety goggles

Skin protection

protective clothing

General protective measures

Do not inhale gases/vapours/aerosols.

**Hygiene measures**

At work do not eat, drink, smoke or take drugs.

9. Physical and chemical properties

Form
aerosol

Colour
colourless, clear

Odour
characteristic

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
Flash point	-60 °C				
Ignition temperature	510 °C				
Lower explosion limit	1,5 Vol-%				
Upper explosion limit	8,5 Vol-%				
Vapour pressure	5000 hPa	20 °C			
Density	0,54 g/ml	20 °C			

Explosive properties

The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .

10. Stability and reactivity**Conditions to avoid**

Keep away from heat.

Formation of explosive gas/air mixtures.

Hazardous decomposition products

Carbon monoxide and carbon dioxide.

No hazardous decomposition products known.

Thermal decomposition

Remark No decomposition if used as directed.

11. Toxicological information**Experiences made from practice**

Irritates respiratory tract.

Inhalation causes narcotic effect/intoxication.

12. Ecological information**General regulation**

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment.



13. Disposal considerations

Waste code No.	Name of waste
15 01 10*	packaging containing residues of or contaminated by dangerous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 91/689/EEC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

General information

For proper waste disposal a complete emptying of the tin is necessary.

14. Transport information

Land and inland navigation transport ADR/RID

UN 1950 AEROSOLS, 2.1, (D), Classification code: 5F
transport in "limited quantities" according to 3.4 ADR LQ2 is possible

Marine transport IMDG

UN 1950 AEROSOLS, 2.1

Air transport ICAO/IATA-DGR

UN 1950 Aerosols, flammable, 2.1

Transport/further information

24h EMERGENCY CONTACT (TRANSPORT) +49(0)178 433 7434 (Consultank Lutz Harder GmbH)

15. Regulatory information

VOC standard	
VOC content	56 %
VOC value	560 g/L

16. Other information

Recommendend uses and restrictions

National and local regulations concerning chemicals shall be observed.

Further information

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Wording of the R/H-phrases specified in chapter 3 (not the classification of the mixture!)

R 12 Extremely flammable.