



1. Identification of the substance/mixture and of the company/undertaking

Product identifier

Name of product Plastic-Metal TI Resin (GB)
Code-Nr. 104301

Manufacturer/distributor

WEICON GmbH & Co. KG
Königsberger Straße 255, DE-48157 Münster
Postbox 84 60, DE-48045 Münster
Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322-244
E-Mail : info@weicon.de
Internet : www.weicon.de

Advice

Abteilung Angebote, Verkauf, Export
Phone ++49(0)251 / 9322 - 0

Emergency advice

Giftnotruf Bonn: Bei Vergiftungen (in case of poisoning)
Phone ++49(0)228-19 240

Recommended intended purpose(s)

2-Component Epoxy Resin - Resin Component

2. Hazards identification

Classification according to 67/548/EEC or 1999/45/EC

Xi; R36/38

R43

N; R51/53

R-phrases

36/38

Irritating to eyes and skin.

43

May cause sensitisation by skin contact.

51/53

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Labelling according to 67/548/EEC or 1999/45/EC

Remarks for labelling

The product is classified and labelled in accordance with EC directives/German regulations on dangerous substances.

Xi Irritant

N Dangerous for the environment

R-phrases

36/38

Irritating to eyes and skin.

43

May cause sensitisation by skin contact.

51/53

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S-phrases

2

Keep out of the reach of children.

24

Avoid contact with skin.

37

Wear suitable gloves.

46

If swallowed, seek medical advice immediately and show this container or label.

61

Avoid release to the environment. Refer to special instructions/safety data sheets.



Hazardous ingredients for labeling

1,6-bis(2,3-epoxypropoxy)hexane, Reaction Product of Phenol-Formaldehyde Novolac and Epichlorohydrin, reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)

Special rules for supplemental label elements for certain mixtures

Contains epoxy constituents. See information supplied by the manufacturer.

3. Composition/information on ingredients

Description

Epoxy resin compound containing mineral fillers.

Hazardous ingredients

| CAS No | EC No | Name | [% weight] | Classification according to 67/548/EEC |
|------------|-----------|---|------------|--|
| 16096-31-4 | 240-260-4 | 1,6-bis(2,3-epoxypropoxy)hexane | 1 - 10 | Xi R36/38; R43; R52/53 |
| 28064-14-4 | polymer | Reaction Product of Phenol-Formaldehyde Novolac and Epichlorohydrin | 1 - 10 | Xi R36/38; R43; N R51/53 |
| 25068-38-6 | 500-033-5 | reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700) | 30 - 50 | Xi R36/38; R43; N R51-53 |

4. First aid measures

General information

If threatening unconsciousness, position and transport in recovery position
In case of breathing difficulties give oxygen.

In case of inhalation

Ensure of fresh air.
In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with soap and water.
Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

In case of ingestion

Do not induce vomiting.
Refer to medical treatment.
If swallowed give water to drink.

Treatment (Advice to doctor)

In the event of pulmonary irritation treat initially with dexamethasone metered-dose aerosol.

5. Firefighting measures

Suitable extinguishing media

Foam
Dry fire-extinguishing substance
Carbon dioxide
Water spray jet

Extinguishing media which must not be used for safety reasons

Full water jet

Special hazards arising from the substance or mixture

Fire gas of organic material has to be classed invariably as respiratory poison.
In fires, hazardous combustion gases are formed:



Nitrogen oxides (NO_x)

Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply (isolated).
Wear full protective clothing.

Additional information

Cool endangered containers with water spray jet.
Collect contaminated firefighting water separately, must not be discharged into the drains.

6. Accidental release measures

Personal precautions

Ensure adequate ventilation.
Use personal protective clothing.
Use breathing apparatus if exposed to vapours/dust/aerosol.

Environmental precautions

Do not discharge into the drains/surface waters/groundwater.
Do not discharge into the subsoil/soil.

Methods for cleaning up

Take up with absorbent material.
After taking up the material dispose according to regulation.

7. Handling and storage

Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.
Open and handle container with care!

Requirements for storage rooms and vessels

Keep in closed original container.

Further information on storage conditions

Store closed container at cool and aired place.

8. Exposure controls/personal protection

Additional advice on system design

Sufficient ventilation and exhaustion.

Respiratory protection

If ventilation insufficient, wear respiratory protection.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: natural rubber, 0,6mm; 480min; 60min;

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Eye protection

tightly fitting goggles

Skin protection

Light protective clothing.

General protective measures

Avoid contact with eyes and skin
Do not inhale gases/vapours/aerosols.



Hygiene measures

At work do not eat, drink and smoke.
Remove soiled or soaked clothing immediately.
Wash hands before breaks and after work.

9. Physical and chemical properties

| | | |
|-------------|---------------|----------------|
| Form | Colour | Odour |
| viscous | grey | characteristic |

Important health, safety and environmental information

| | Value | Temperature | at | Method | Remark |
|----------------------------|-----------------------|-------------|----|--------|-----------|
| Flash point | > 100 °C | | | | |
| Density | 1,7 g/cm ³ | 20 °C | | | |
| Solubility in water | | | | | insoluble |

10. Stability and reactivity

Materials to avoid

Reactions with strong acids and alkalis.
Reactions with strong oxidising agents.

Hazardous decomposition products

Nitrous oxides (NO_x)
risk of formation of toxic pyrolysis products

11. Toxicological information

Acute toxicity/Irritability/Sensitization

| | Value/Validation | Species | Method | Remark |
|---------------------------|------------------|------------|--------|--------|
| Irritability skin | irritant | | | |
| Irritability eye | irritant | | | |
| Skin sensitization | sensitizing | Guinea pig | | |

Additional information

Labelling in compliance with the assessment procedure specified in the EC guidelines 1999/45/EC.

12. Ecological information

General regulation

Do not allow uncontrolled leakage of product into the environment.
Product is not allowed to be discharged into aquatic environment.



13. Disposal considerations

Recommendations for the product

Remove in accordance with local official regulations.

There are no harmonised regulations on the disposal of chemicals in the member states of the EU. In Germany, the Recycling and Waste Management Act 8 KrW-/AbfG stipulates recycling as a requirement.

This means that a distinction must be made between "wastes for recycling" and "wastes for disposal". Particular aspects - in the main concerning delivery - are also governed by the Laender.

Recommendations for packaging

Empty containers can be deposited after cleaning in accordance with the local waste regulations.

14. Transport information

Land and inland navigation transport ADR/RID

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy-Harz), 9, III, (E), Classification code: M6

Marine transport IMDG

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy-resin), 9, III, MARINE POLLUTANT

Air transport ICAO/IATA-DGR

UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Epoxy-resin), 9, III

Transport/further information

24h EMERGENCY CONTACT (TRANSPORT) +49(0)178 433 7434 (Consultank Lutz Harder GmbH)

15. Regulatory information

16. Other information

Recommendend uses and restrictions

National and local regulations concerning chemicals shall be observed.

Further information

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Wording of the R/H-phrases specified in chapter 3 (not the classification of the mixture!)

R 36/38 Irritating to eyes and skin.

R 43 May cause sensitisation by skin contact.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.