

New Products 2011

WEICONLOCK® White-Line

The new »White Line« for increased health protection and safety at work. The new formulas also enable use in sensitive production areas. Three types of the »White Line« have a »white« EC safety data sheet and are therefore marking-free and meet strict requirements of plant physicians.

Overview of types:

- AN 301-43** Threadlocking, medium-strength,
– marking-free –
- AN 301-70** Threadlocking, high-strength,
– marking-free –
- AN 301-72** Pipe and flange sealing with PTFE, medium-strength, resistant to high temperatures,
– marking-free –
- AN 301-38** Retaining cylindrical assemblies, high-strength
- AN 301-48** Retaining cylindrical assemblies, high-strength, resistant to high temperatures

Delivery forms:

20 ml, 50 ml and 200 ml PEN; AN 301-72 in 50 ml and 200 ml



WEICON Thread Sealing Cord DF 175

DF 175 is a patented thread sealing cord made of 100% PTFE that seals almost all metal and plastic threads permanently and safely. The Thread Sealing Cord is extremely resistant to almost all chemicals. DF 175 is non-flammable and operates reliably in a temperature range from -200°C (-328°F) to +240°C (+464°F), is durable for an unlimited period of time and stays permanently soft and elastic.

Delivery form: 175 m plastic can Art.-No.: 30010175-5



WEICON Contact VA 30 Black

One-component cyanoacrylate adhesive. Special rubber-filled type with black colour. Ideal for bonding rubber materials (e. g. solid rubber, cellular rubber, etc.), plastics as well as metal to plastic. Medium viscosity (200-300 mPa-s), residual elasticity after curing.

Delivery forms:

12 g PEN Art.-No.: 12603012

30 g PEN Art.-No.: 12603030

60 g PEN Art.-No.: 12603060

WEICON Flex 310 M® 2 K fast-curing

Fast-curing, elastic two-component adhesive and sealant on a hybrid polymer basis. Due to the pre-defined and process-safe curing system, it is ideal for series production. Good adhesion on nearly all materials, even without primer. Free of solvents, isocyanate and substances that hinder painting (e. g. silicone).

Delivery form: 250 ml cartridge Art.-No. 13305250





WEICON Bio-Fluid

High-purity medical-grade white oil, free of resins and acids, specially developed for applications in the food, beverage, pharmaceutical and cosmetic industries.

Delivery forms:

200 ml Spray can Art.-Nr.: 11600200 NEW

500 ml Spray can Art.-Nr.: 11600500

Bio-Fluid conforms with:

- The "Paraffinum Subliquidum" as defined in the German pharmacopeia ("Deutsches Arzneibuch", DAB 10).
- The NSF classification H1 for the direct contact with food.

NSF = Non-food Compounds Registration Programme

WEICON Aluminium Paint

Aluminium Paint is made on the basis of metal pigments and offers a high-quality and abrasion-resistant corrosion protection for all metal surfaces. The coating has a good resistance against thinned lyes and acids as well as against weathering influences, for e.g. metal structures, doors, gates, railings and grilles, gardening implement and containers, vehicles and wheel rims.

Delivery forms:

375 ml can Art.-No.: 15002375, 750 ml can Art.-No.: 15002750

WEICON Stainless Steel Paint

Stainless Steel Paint is a corrosion- and weathering-resistant surface coating based on metal pigments. Due to its excellent resistance to chemicals, Stainless Steel Paint can be used in all applications where an efficient and optically attractive protection layer is required. Among other substances, the alloy contains chrome, nickel and manganese. Stainless Steel Paint resists abrasion and is tack-free.

Delivery forms:

375 ml can Art.-No.: 15004375, 750 ml can Art.-No.: 15004750

WEICON Mini-Solar No. 3

For stripping of all common solar cables of 1.5 to 6.0 mm Ø. Strips also flexible cables such as 3 x 0.75 mm², 10 mm² and 16 mm². The new ergonomic handle form allows faster and more convenient stripping. Needs no adjustment of the cutting depth.

Working range:

1.5 – 2.5 mm², 4.0 – 6.0 mm² (15 – 9 AWG)

Side cutter: max. 4.0 mm² (11 AWG)

Adjustable length stop: 6 – 28 mm (1/4 – 1 inch)

Art.-No.: 52002003



WEICON GmbH & Co. KG

Königsberger Str. 255 · DE-48157 Münster
P.O. Box 84 60 · DE-48045 Münster · Germany

Tel. +49 (0) 251 / 93 22-0
Fax +49 (0) 251 / 93 22-244
Fax +49 (0) 251 / 93 22-233 Export
www.weicon.de · info@weicon.de

**WEICON
Middle East L.L.C.**
Jebel Ali Ind Area 3
P.O. Box 118 216
Dubai · U.A.E

Phone +971 4 880 25 05
Fax +971 4 880 25 09
Mobile +971 50 545 99 83
www.weicon.ae
info@weicon.ae

WEICON Inc.
20 Steckle Place · Unit 20
Kitchener · Ontario N2E 2C3
Canada

Phone +1 519 896 5252
Fax +1 519 896 5254
Cell +1 519 590 5168
www.weicon.ca
info@weicon.ca

Distributed by:

Detailed information on these products is available from our single brochures and at www.weicon.de

The specifications and recommendations given in this brochure must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.