

**new
packaging**



Flex+bond®

Highly elastic and strong adhesive / sealant

WEICON's Flex+bond remarkable features are its wide range of application possibilities and the high adhesive force.

It bonds and seals nearly all materials such as metals, wood, plastics, glass, ceramics to themselves and among each other and is therefore the excellent product for a great variety of repairs and bondings as well as for the sealing of seams and joints.

WEICON Flex+bond is a one-component product, remains permanently elastic and can be sanded after curing and overpainted (wet in wet).

WEICON Flex+bond is:

- permanently elastic
- temperature resistant from -40°C (-40°F) up to +90°C (+194°F), briefly (2-3 hours, except transparent) up to +130°C (+266°F)
- resistant to weathering and UV rays
- resistant to salt water
- neutral in odour
- overpaintable (wet in wet)
- cures nearly shrinkage- and bubbling-free
- sandable
- resistant to ageing
- free of isocyanate and solvents
- free of silicone, halogen and PVC



Packaging:

12 x 85 ml	Colour white	Art.-No.: 13350085
12 x 85 ml	Colour black	Art.-No.: 13352085
12 x 85 ml	Colour grey	Art.-No.: 13351085
12 x 85 ml	Colour transparent	Art.-No.: 13353085
Sales display 4	Colours 3 pcs. each	Art.-No.: 13359085


WEICON GmbH & Co. KG

Königsberger Str. 255 • DE-48157 Münster
Postfach 84 60 • DE-48045 Münster
Tel. +49 (0) 251 / 93 22-0
Fax +49 (0) 251 / 93 22-244
Fax +49 (0) 251 / 93 22-233 Export
www.weicon.de • info@weicon.de

WEICON Middle East L.L.C.

Jebel Ali Ind. Area 3
P. O. Box 118216, Dubai – U.A.E
Phone +971 4 880 25 05
Fax +971 4 880 25 09
Mobile +971 50 545 99 83
www.weicon.ae • info@weicon.ae

Distributed by:



Any product specifications and recommendations given herein must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do warrant the continuously high quality of our products being free from defects in accordance with and subject to our General Sales Conditions. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.