

Anti-Friction Spray MoS₂



dry lubricant

Anti-Friction Spray MoS₂ is a grease-free dry lubricant with pressure and temperature resistance from -185°C (-301°F) to +400°C (752°F). The layer repels dust, dirt and water, resists oils, greases and many chemicals and adheres to metals, plastics and wood surfaces.

The high portion of MoS₂ provides clean sliding lubrication, reduces friction, has excellent emergency running properties and reduces running noises.

WEICON Anti-Friction Spray MoS₂ shortens and improves the slide-in conditions for sliding bearings, gearings and other slide pairings, particularly at high pressure load and low sliding speed.

WEICON Anti-Friction Spray MoS₂ can be used on sliding and running rails and guides, conveyor belts, transport rollers and slides, as a coating for cutting, on loading technology products, as a substitute for release agents containing silicone, and wherever oil or grease lubrication is not permitted or desired.

Technical Data

Odour	solvent
Features	dry lubricant on MoS ₂ basis
Storage stability	24 months
Colour	anthracite black
Temperature resistance	-185 to +400 °C
ISSA-Code	53.402.27
IMPA-Code	45 08 52

Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

Processing

Clean and degrease surfaces prior to application (e. g. WEICON Surface Cleaner). Shake can until rattle of mixing ball is heard. Spray on cleaned and dry surfaces from about 20 cm distance. In case of continued use, shake can again from time to time. At room temperature (+20°C/+68°F), the coating is dust-dry approx. 15 minutes after spraying.

Storage

Pressurized container: protect from sunlight and do not expose to temperatures exceeding +50°C.

Safety and health

When using WEICON products, the physical, safety technical, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Available sizes:

11539400 Anti-Friction Spray MoS₂ 400 ml

Accessories:

11202500 Cleaner Spray S, 500 ml
11850200 Hand Protective Foam, 200 ml

WEICON GmbH & Co. KG
(Headquarters)
Germany
phone +49 (0) 251 9322 0
info@weicon.de

WEICON Middle East L.L.C.
United Arab Emirates
phone +971 4 880 25 05
info@weicon.ae

WEICON Inc.
Canada
phone +1 877 620 8889
info@weicon.ca
www.weicon.ca

WEICON Kimya Sanayi Tic. Ltd. Şti.
Turkey
phone +90 (0) 212 465 33 65
info@weicon.com.tr
www.weicon.com.tr

WEICON Romania SRL
Romania
phone +40 (0) 3 65 730 763
office@weicon.com

WEICON SA (Pty) Ltd
South Africa
phone +27 (0) 21 709 0088
info@weicon.co.za

WEICON South East Asia Pte Ltd
Singapore
phone (+65) 6710 7671
info@weicon.com.sg

WEICON Czech Republic s.r.o.
Czech Republic
phone +42 (0) 417 533 013
info@weiconcz.cz

WEICON Ibérica S.L.
Spain
phone +34 (0) 914 7997 34
info@weicon.es